

# USB Speaker Tracking Camera




AMC-G200TH


## Features

- Implemented with audio positioning and intelligent face detection algorithm;
- Has a tracking camera & an EPTZ 4K full-view camera;
- Full-view EPTZ camera can automatically frame all the meeting participants;
- Auto switch between close-up image and full-view image;
- Support echo cancellation;
- Support HDMI, USB2.0, 3G-SDI & network interface, up to 1080P60 resolution;
- Support H.264/H.265/MJPEG video compression.

## Dimensions



## Accessories



## Technical Data

Model	AMC-G200TH
<b>Camera</b>	
Image Sensor	1/2.8" CMOS, 2.14MP
Focal	f=3.9mm-46.8mm
Iris	F1.6-F2.8
Zoom	Optical:12X, Digital:12X
FOV	Horizontal 72.5° - 6.3°
Focus	Auto, Manual, PTZ Push, One Push
Shutter Speed	1/25 ~ 1/10,000s
AGC	Auto, Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Auto Tracking
Exposure	Auto, Manual, Shutter Priority, Iris Priority
SN Ratio	≥50dB
BLC	Support
<b>Full View Camera</b>	
Image Sensor	1/2.5" 4K CMOS Sensor, 8.57MP
Lens	2.8mm focal length, 4X digital zoom
FOV	98°
DNR	2D/3D
Video Adjustment	Support EPTZ
<b>PTZ</b>	
Pan	-90° ~ +90°, 0.1° ~ 100°/s
Tilt	-30° ~ +90°, 0.1° ~ 80°/s
Preset Number	64
<b>Network</b>	
Max Image Size	1080P60
Video Compression	H.264/H.265/MJPEG
Audio Compression	AAC
Protocol	HTTP, RTSP, RTMP, RTP, TCP, UDP, ONVIF
Multi-Stream	Support 1×close-up view, 1×full view, 1×switched between view
<b>Interface</b>	
SDI	1×3G-SDI, Video Format: 1080P60/50/30/25, 720P60/50
HDMI	1×HDMI, Video Format: Same as SDI
USB	1×USB2.0, support UVC/UAC
Audio Input	2×3.5mm Line In, including 1 channel AEC reference audio input
Network Interface	10M/100M RJ45
<b>General</b>	
Control Protocol	VISCA
Address	1 - 6
Power	DC12V
Power Consumption	<20W
Operating Environment	Temperature: 0°C ~ +40°C, Relative Humidity: 10%RH ~ 90 %RH
Storage Environment	Temperature: -20°C ~ +60°C, Relative Humidity: 10%RH ~ 95 %RH
Dimension (LxWxH)	245mmx145mmx165mm
Weight	< 2KG