

# Interactive Audio Array System

## APS-J0502Q/S



Spherical  
Microphone  
AMU-B3X



Gun-Type  
Sector Array  
AMU-G3S



Front  
Interactive Audio Array Processor  
APS-J0502



Back

## Features

- Built-in spherical array positioning tech to identify speaker voice precisely from disturbing sound sources;
- Mono and stereo echo cancellation to achieve non-linear noise suppression at high volume up to 100dB;
- 3D Spatial Audio Algorithms, beamforming technology and Holographic sound field restoration;
- Built-in quad-core A53 1.5GHz processor with beamforming and voice pickup technologies such as AGC, AEC, ANC AEC to meet various requirements;
- With 3-microphone array, the system supports 120 degree and 360-degree voice pickup;
- Powerful processing performance, it's the perfect solution for different application remote interaction and high-quality class recording;
- Built-in rich interfaces, supports external wireless microphones, and other inputs to achieve automatic fusion of different HD audio sources;
- Easy to install and maintain, and efficiently matches the environment;
- Supports external sound devices, compatible with other local and cloud audio/video systems.

## Application

**Education:** education and training classes;

**Conference:** local and remote meetings, Large lecture halls, Corporate boardrooms, Corporate training rooms etc.;

**Others:** Auditoriums, Museums, hospitals, command centers, briefing centers etc.

### Package A : APS-J0502Q

Component: 1\*array interactive audio Processor+2\*(With Connector and Canon head audio line)  
APS-J0502+2\*AMU-B3X Applicable: Most interactive scenarios

### Package B : APS-J0502S

Component: 1 \*Array Interactive Audio Processor + 1 \*Spherical Star Array Microphone  
(with connector and Canon Cable) + 1 \*Shotgun Sector Array Microphone  
APS-J0502+AMU-B3X+AMU-G3S  
Applicable: Focus on the sound collection of lecturers and speakers

## Technical Data

### APS-J0502

#### Sampling Rate

48kHz

#### Frequency Response

100Hz ~ 20KHz

#### Distortion Degree

≤0.1%

#### SNR

≥75dB

#### Acoustic Feedback Gain

≤18dB

#### Noise Reduction Amplitude

≤30dB

#### Echo Cancellation

≤90dB

#### Reverberation Suppression

≤18dB; Echo cancellation length≤1s

#### Supported Algorithms

AEC, AGC, ANC, AFC and reverberation suppression etc.

### AMU-B3X

#### Sensitivity

35dB±3dB

#### Frequency Response

100Hz ~ 20KHz

#### Distortion Degree

≤0.1%

#### SNR

≥75dB

#### Directivity

Omnidirectional (360 degree omnidirectional pickup)

#### Microphone Array (Single)

3 φ10mm condenser microphone star array

#### Pickup Range(Single)

6m\*6m

#### Interface Connector

6-pin XLR head for connecting special connector and ball mic; RJ45, For connection to audio processorFor connection to audio processor

#### Professional Connector

Indicator light: green light on: normal work; light off: not connected

Interface: 6-pin XLR head for connecting special connector and ball mic; RJ45 interface for connecting audio processors

Power supply and transmission: Super five twisted pair shielded cable realizes audio transmission and microphone power supply at the same time through the network port

### AMU-G3S

#### Sensitivity

-35dB±3dB

#### Frequency Response

100Hz ~ 20KHz

#### Distortion Degree

≤0.1%

#### SNR

≥75dB

#### Directivity

120 degree scalloped Point Pickup

#### Microphone Array(Single)

3 imported condenser microphones, sector array

#### Pickup Range(Single)

30 m<sup>2</sup> fan-shaped pointing area (120° straight line 5m)

#### Operating Temperature

-10°C ~ +50°C

#### Storage Temperature

-20°C ~ +70°C

#### Microphone Interface

RJ45 interface for connecting microphones and audio processors

#### Power

DC12V

#### Power Supply

Realize audio transmission and microphone power supply at the same time through the network port