4K Video Soundbar

AMC-G309UV2





Features

- Integrated design of video cam, microphones and speakers, easy setup of remote video conference;
- Smart and precise positioning of speaker and auto framing, giving best view of speaker and all attendees;
- 4K UHD video for superb experience;
- HFOV up to 110°, full cover of meeting room;
- Built-in high-sense mic array, pickup range up to 5 meters, supporting AGC, AEC, ANC;
- Supporting 2 external cascade microphones to extend pickup range up to 12 meters;
- Speaker with Passive diaphragm design with enhanced bass experience;
- USB3.0 interface, supporting MJPEG/H.264/H.265 data;
- Built-in Bluetooth for easy connection of external devices;
- Compatible with main cloud platforms such as Zoom and Microsoft Teams etc.;
- Equipped with bracket for TV installation.

Technical Data

Camera Image Sensor 1/2.8" 4K CMOS, 8.46MP Iris F2.2 Focal Length f=2.1mm **Digital Zoom** 4x FOV Horizontal: 110°. Vertical: 74° EPTZ Support **Min Focus Distance** 50cm Video Output Format 4KP30 Exposure Auto, Manual, Shutter Priority White Balance Auto, Manual DNR 2D/3D Image Flip Flip/Mirror

Audio

Built-in Mic 4 MIC array Pick-up Distance 5 meters Audio Process AEC/ANC/AGC

USB

1xUSB3.0, Type B. Support UVC 1.0 MJPEG/H.264/H.265 MJPEG: 4KP30/P25, 1080P30/P25, 720P30/P25, 360P30/P25 H.264: 4KP20, 1080P30/P25, 720P30/P25, 360P30/P25, 720P30/P25, 360P30/P25

Other

Network Interface RJ45, 10M/100M Remote Control Support Mic Extension Support

General

Power DC12V; <8W Dimension (L×W×H) 603mm×74mm×93mm Operating Temperature 0°C ~ +40°C Storage Temperature -20°C ~ +60°C Weight ≤2kg

EPTZ

EPTZ Support

Microphone EM-01

SNR 69dB Pick-up Distance 3 Meters, 360°

Cascade Number Support up to two Dimensions (L×W×H) 90mm×90mm×36mm