


# 4K EPTZ Camera

## ZC5-F20N



ZC5-F20N



## Features

- 1/2.8" CMOS sensor, 8.46 MP;
- 121°HFOV, enable to frame more, with no distortion;
- Supports EPTZ;
- Video resolution up to 4KP30, H.265/ H.264 video compression;
- With OSD menu;
- Support stand and ceiling installation;
- POE supported;
- Support student locating.

## Technical Data

### Camera

#### Image Sensor

1/2.8" CMOS, 8.46 MP

#### Focal Length

f=1.64mm

#### Iris

F=2.4

#### HFOV

Horizontal 121°

#### Shutter Speed

1/60~1/10,000s

#### AGC

Auto, Manual

#### White Balance

Auto, Manual, One Push

#### AE Control

Auto, Manual, Shutter Priority

### Interface

#### Network

RJ45 (10M/100M), optional POE

1.Up to 4KP30

main stream: 1080P30/25, 720P30/25, 360P30/25

sub stream: 4KP30/25, 1080P30/25, 720P30/25, 360P30/25

Image compression  
H.264/H.265

Support HTTP/TCP  
/UDP/RTSP/RTMP/ONVIF  
Support AAC

#### USB 2.0

1.Support UVC

2.Image compression  
H.264/H.265/MJPEG; support  
4K, 1080P, 720P, 360P

Platform OS: Windows  
7/8/10, Mac OS, Android OS

#### Audio Interface

1 × LINE IN

### General

#### Control Protocol

VISCA

#### Power

DC12V; <5W

#### Address

0~63

#### Operating Temperature

0°C ~ +40°C

#### Storage Temperature

-20°C ~ +60°C

#### Dimensions(W×D×H)

149 mm×76 mm×58mm

#### Weight

<0.5kg