


4K EPTZ Camera

ZC5-F20N



ZC5-F20N



- LAN
- USB 2.0
- LINE IN
- Power Indicator
- DC 12V

Features

- 1/2.8" CMOS sensor, 8.46 MP;
- 121°HFOV, enable to frame more, with no distortion;
- Support EPTZ;
- Video resolution up to 4KP30, H.265/ H.264 video compression;
- With OSD menu;
- Support stand and ceiling installation;
- POE supported;
- Support student locating.

Technical Data

Camera

Image Sensor

1/2.8" CMOS, 8.46 MP

Focal Length

f=1.64mm

Iris

F=2.4

HFOV

Horizontal 121°

Shutter Speed

1/60~1/10,000s

AGC

Auto, Manual

White Balance

Auto, Manual, One Push

AE Control

Auto, Manual, Shutter Priority

Interface

Network

RJ45 (10M/100M), optional POE

1. Up to 4KP30
main stream: 1080P30/P25, 720P30/P25, 360P30/P25
sub stream: 4KP30/P25, 1080P30/P25, 720P30/P25, 360P30/P25

2. Image compression
H.264/H.265

3. Support HTTP/TCP
/UDP/RTSP/RTMP/ONVIF

4. Support AAC

5. Browser access supported.

USB 2.0

1. Support UVC

2. Image compression
H.264/H.265/MJPEG; support
4KP30/P25, 1080P30/P25,
720P30/P25, 360P30/P25

Platform OS: Windows
7/8/10, Mac OS, Android OS

Audio Interface

1 × LINE IN

General

Control Protocol

VISCA

Power

DC12V; <5W

Address

0~63

Operating Temperature

0°C ~ +40°C

Storage Temperature

-20°C ~ +60°C

Dimensions(W×D×H)

149 mm×76 mm×58mm

Weight

<0.5kg