

IP Keyboard Controller



CKB-06

Features

- Camera control in IP and analog modes;
- Full VISCA, ONVIF, PELCO-P/D protocols;
- The built-in web server makes configuration interface simple and clear;
- Support POE;
- 7 buttons to switch 7 cameras;
- 4D joystick control;
- Rocker switch controls zoom speed;
- Shortcut keys/knobs for common settings;
- TFT LCD screen display.

Technical Data

Model	CKB-06
White Balance	Button. Auto Indoor Outdoor One Push Manual
Exposure	Button. Auto, Manual, Shutter Priority, Iris Priority
Shortcut Button	Bright Adjustment, Exposure Gain, BLC Focus Model Selection, OSD
Shortcut Knob	RB Gain, Iris, Pan/Tilt Speed(1-8 Steps) Zoom speed(1-8 Steps)
Protocol	Full VISCA, PELCO-D/P, ONVIF
Output	RS422, RS232, RS485, RJ45
Joystick	4D joystick
Screen	TFT LCD 320×240
Power Consumption	≤5W
Power	DC12V-2A
Work Temperature	20%80% (non-condensation)
Work Humidity	321.6mm×179.2mm×105.7mm)
Dimensions (L×W×H)	1.63KG
Weight	

Dimensions

