


4K PTZ Camera

AMC-G403



- 1 USB 3.0
- 2 LINE IN
- 3 LAN
- 4 DC 12V

Features

- 1/2.8" CMOS, 8.46MP;
- 3x lossless zoom @ 4K video output, 6x lossless zoom @ 1080P video output, 9x lossless zoom @ 720P video output, with a maximum HFOV up to 81.4°;
- USB 3.0 with max 4K video output;
- Standard UVC/UAC protocol;
- H.265/H.264 video compression;
- Network and USB 3.0 outputs;
- Dual stream.

Technical Data

Camera

Image Sensor

1/2.8" CMOS, 8.46MP

Optical Zoom

3x

Focal Length

f=3.3mm ~ 9.7mm

Iris

F2 ~ F3.7

HFOV

81.4° ~ 31.3°

Digital Zoom

5x

Focus System

Auto, Manual, PTZ Trigger, One Push Trigger

Shutter speed

1/50 ~ 1/10,000s

Lowest Illumination

1.0Lux (Color)

AGC

Auto, Manual

White Balance

Auto, Manual, Auto Tracking, One Push, Specified Color Temperature

BLC

Support

Wide Dynamic

Support

Exposure

Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority

SNR

≥50dB

General

Power

DC12V; <12W

Operating Temperature

0°C ~ +40°C

Storage Temperature

-20°C ~ +60°C

Dimensions (L*W*H)

176mm × 137mm × 171mm

Weight

≤1.2kg

PTZ

Pan

-170°~+170°; 0.1°~120°/s

Tilt

-30°~+90°; 0.1° ~ 90°/s

Image Filp

Support

Preset Number

256

Interface

Network

1 × RJ45: 1×10M/100M

1. Image Compression: H.264/H.265: 4KP30/P25, 1080P60/P50/P30/P25, 720P60/P50/P30/P25

2. Protocol: ONVIF/RTSP/RTMP/TCP/UDP /SRT/RTMPS/GB28181

3. Audio Compression: AAC/G.711

4. Multi-Streams

USB 3.0

1. Support UVC1.1

2. UVC Support:

H.264/H.265/MJPEG: 4KP30/P25, 1080P30/P25, 720P30/P25

YUY2/NV12: 1080P30/P25, 720P30/P25

3. UAC Audio Format PCM

Audio

1 × LINE IN, 3.5mm